

MULTIBOX 25

Made of hot-pressed glassfibre reinforced polyester (GRP)
 Two-part construction, so that equipment can be installed in either the shallow or the deep part.
 Stackable design for space saving storage and transport
 Low flammability and self-extinguishing
 4 mounting elements in 316 stainless steel

- Color: light gray, RAL 7032
- EPDM seal
- Weight approx. 13.2lbs, 6kg
- UV-resistant
- Protection class IP65

For further technical details → data sheet [KD015](#) & [KD112](#)

Dimensions	Height	Width	Depth
in inch (approx.)	19.1" x	15.2" x	9.5"
in mm (approx.)	485 x	385 x	240

Heat transition coefficient K	without window	with window
without isolation	2.5 W/K	2.9 W/K
arctic-GRP	0.9 W/K	1.3 W/K

- Designs** (Locking-type see data sheet [KD152](#))
- SV4** 4 latches in 316 stainless steel (standard)
 - SE2** 2 hinges and 2 latches in 316 stainless steel with angle for optional padlock

Lid Propstay (only design SE)

- LP** in plated steel
 - LPSS** in stainless steel
- } 1 pc.
 2 pcs.

Window

- FA** acrylic glass window
 - FS** safety glass window
- } mounted in TE
 TU

arctic additional Insulation

- PU foam, not stackable
- arctic-GRP** GRP lining

Explosion Protection

- GO** antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0
- Ex p** preparation for pressurization according to DIN EN IEC 60079-2

Protection Class

- IP66** **IP67** **IP68**
- CSA Enclosure Type 4X (NEMA 4X)**

Vents and Drains (see data sheet [KD184](#))

- LF** Labyrinth filter IP44
- DV** Vents and Drains IP66

