

# MULTIBOX 80

Made of hot-pressed glassfibre reinforced polyester (GRP)  
 Two-part construction, so that equipment can be installed in either the shallow or the deep part.  
 Stackable design for space saving storage and transport  
 Low flammability and self-extinguishing  
 4 mounting elements in 316 stainless steel

- Color: light gray, RAL 7032
- EPDM seal
- Weight approx 20.9lbs, 9,5kg
- UV-resistant
- Protection class IP65

For further technical details → data sheet [KD015 & KD112](#)

Dimensions	Height	Width	Depth
in inch (approx.)	29.5"	x 20.5"	x 9.8"
in mm (approx.)	750	x 520	x 250

Heat transition coefficient K	without window	with window
standard	6.8 W/K	7.2 W/K
arctic-GRP	1.8 W/K	2.5 W/K

**Designs** (Locking-type see data sheet [KD152](#))

- SV4** 4 latches in stainless steel (standard)
- SE2** 2 hinges and 2 latches in 316 stainless steel, with angle for optional padlock

**Lid Propstay** (only design SE)

- LP** in plated steel
  - LPSS** in stainless steel
- }  1 pc.  
 2 pcs.

**Window**

- FA** acrylic glass window
  - FS** safety glass window
- } mounted in  
 TE  
 TU

**arctic additional Insulation**

- PU foam, not stackable  
 **arctic-GRP** GRP lining

**Explosion protection**

- GO** antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0
- Ex p** preparation for pressurization according to DIN EN IEC 60079-2

**Protection Class**

- IP66**  **IP67**  **IP68**
- CSA Enclosure Type 4X (NEMA 4X)**

**Vents and Drains** (see data sheet [KD184](#))

- LF** Labyrinth filter IP44
- DV** Vents and Drains IP66

