

CLASSIC 210.135.xxx - double door

Reinforced glassfibre polyester parts, sandwich construction, insulated with polyurethane foam core
 Corner posts of GRP with vertical c-rails
 Textured surface in grey RAL 7032
 Protection class IP 54

Vertical c-rails provided at the side wall and rear wall
 Door with 3-point locking device single lever handle and basquill-locking-device for left door and overlapflange of stainless steel
 Roof overhang 25mm/ 1.0" all around


Arrangement

Floor (see data sheet [SD522](#) "Floor versions for classic series")

Options

- MP** Mounting plate
- FA/FS** Acrylic glass/ Safety glass window
- SG** swing handle with key lock burglary resistant

- C-VA** Vertical c-rails in stainless steel instead of aluminium
- GO** antistatic to avoid electrostatic charges according to EN IEC 60079-0
- SB** Floor fastening (see data sheet [SD523](#) "Fastenings for classic-floor versions design ...")
- WA** Wall fastening inside/ outside
- SZ** Ground vaul



* clear width

Dimensions in mm/ inches

Type	Sizes (mm / inches) with floor		
	H	B	T
210.135.050			500/ 19.7
210.135.070	2140/	1350/	700/ 27.6
210.135.090	84.3	53.2	900/ 35.4
210.135.110			1100/ 43.3

