

# MULTIBOX 25

Made of hot-pressed glass fibre reinforced polyester (GRP)  
 Two-part construction, equipment can be installed in either the shallow or deep part.  
 Stackable design for space saving storage and transport  
 Low flammability and self-extinguishing  
 4 mounting elements in stainless steel

- Colour light grey, RAL 7032
- EPDM seal
- Weight approx. 6kg
- UV-resistant
- Protection class IP65

For further technical details → data sheet [KD015](#) & [KD112](#)

Dimensions      Height      Width      Depth  
 in mm (approx.)    485      x      385      x      240

| Heat transition Coefficient K | without window | with window |
|-------------------------------|----------------|-------------|
| without isolation             | 2,5 W/K        | 2,9 W/K     |
| arctic-GRP                    | 0,9 W/K        | 1,3 W/K     |

**Designs** (Locking-type see data sheet [KD152](#))

- SV 4**    4 clasps in stainless steel (standard)
- SE 2**    2 hinges and 2 clasps in stainless steel, with angle for optional padlock

**Lid Propstay** (only design SE)

- DF**    in galvanized steel
  - DFVA** in stainless steel
- }  1 pc.  
 2 pcs.

**Window**

- FA**    acrylic glass window
  - FS**    safety glass window
- } mounted in  
 TE  
 TU

**arctic additional Insulation**

PU-foam, not stackable

- arctic-GRP** GRP lining

**Explosion Protection**

- GO**    antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0
- Ex p**    preparation for pressurization according to DIN EN IEC 60079-2

**Protection Class**

- IP66**                       **IP67**                       **IP68**
- CSA Enclosure Type 4X (NEMA 4X)**

**Vents and Drains** (see data sheet [KD184](#))

- LF**                      Labyrinth filter IP44
- DV**                      Vents and Drains IP66

