

MULTIBOX 25

Made of hot-pressed glass fibre reinforced polyester (GRP)
 Two-part construction, equipment can be installed in either the shallow or deep part.
 Stackable design for space saving storage and transport
 Low flammability and self-extinguishing
 4 mounting elements in stainless steel

- Colour light grey, RAL 7032
- EPDM seal
- Weight approx. 6kg
- UV-resistant
- Protection class IP65

For further technical details → data sheet [KD015](#) & [KD112](#)

Dimensions Height Width Depth
 in mm (approx.) 485 x 385 x 240

| Heat transition Coefficient K | without window | with window |
|-------------------------------|----------------|-------------|
| without isolation | 2,5 W/K | 2,9 W/K |
| arctic-GRP | 0,9 W/K | 1,3 W/K |

Designs (Locking-type see data sheet [KD152](#))

- SV 4** 4 clasps in stainless steel (standard)
- SE 2** 2 hinges and 2 clasps in stainless steel, with angle for optional padlock

Lid Propstay (only design SE)

- DF** in galvanized steel
 - DFVA** in stainless steel
- } 1 pc.
 2 pcs.

Window

- FA** acrylic glass window
 - FS** safety glass window
- } mounted in
 TE
 TU

arctic additional Insulation

PU-foam, not stackable

- arctic-GRP** GRP lining

Explosion Protection

- GO** antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0
- Ex p** preparation for pressurization according to DIN EN IEC 60079-2

Protection Class

- IP66** **IP67** **IP68**
- CSA Enclosure Type 4X (NEMA 4X)**

Vents and Drains (see data sheet [KD184](#))

- LF** Labyrinth filter IP44
- DV** Vents and Drains IP66

