

MULTIBOX 48

Made of hot-pressed glass fibre reinforced polyester (GRP)
 Two-part construction, equipment can be installed in either the shallow or deep part.
 Stackable design for space saving storage and transport
 Low flammability and self-extinguishing
 4 mounting elements in stainless steel

- Colour light grey, RAL 7032
- EPDM seal
- Weight approx. 7kg
- UV-resistant
- Protection class IP65

For further technical details → data sheet [KD015](#) & [KD112](#)

Dimensions in mm (approx.) Height 485 x Width 385 x Depth 380

Heat transition Coefficient K	without window	with window
without isolation	4,4 W/K	4,9 W/K
arctic-GRP	1,2 W/K	1,6 W/K

Designs (locking-type see data see [KD152](#))

- SV4** 4 clasps in stainless steel (Standard)
- SE2** 2 hinges and 2 clasps in stainless steel, with angle for optional padlock

Lid Propstay (only design SE)

- DF** in galvanized steel
 - DFVA** in stainless steel
- } 1 pc.
} 2 pcs.

Window

- FA** acrylic glass window
 - FS** safety glass window
- } mounted in
} TE
} TU

arctic additional Insulation

- PU-foam, not stackable
- arctic-GRP** GRP lining

Explosion Protection

- GO** antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0
- Ex p** preparation for pressurization according to DIN EN IEC 60079-2

Protection Class

- IP66** **IP67** **IP68**
- CSA Enclosure Type 4X (NEMA 4X)**

Vents and Drains (see data sheet [KD184](#))

- LF** Labyrinth filter IP44
- DV** Vents and Drains IP66

