

# MULTIBOX 170

Made of hot-pressed glass fibre reinforced polyester (GRP)  
 Two-part construction, equipment can be installed in either the shallow or deep part.  
 Stackable design for space saving storage and transport  
 Low flammability and self-extinguishing  
 4 mounting elements in stainless steel

- Colour light grey, RAL 7032
- EPDM
- Weight approx. 12,5kg
- UV-resistant
- Protection class IP65

For further technical details → see data sheet [KD015](#) & [KD112](#)

Dimensions in mm (approx.)      Height 750 x Width 520 x Depth 480

Heat transition coefficient K	without window	with window
Standard	9,1 W/K	9,8 W/K
arctic-GRP	2,4 W/K	3,1 W/K

**Designs** (Locking-type → data sheet [KD152](#))

- SV4** 4 clasps in stainless steel (standard)
- SE2** 2 hinges and 2 clasps in stainless steel, with angle for optional padlock

**Lid Propstay** (only design SE)

- DF** in galvanized steel
  - DFVA** in stainless steel
- }  1 pc.  
 2 pcs.

**Window**

- FA** acrylic glass window
  - FS** safety glass window
- } mounted in  TE  TU

**arctic additional Insulation**

- PU-foam, not stackable
- arctic-GRP** GRP lining

**Explosion Protection**

- GO** antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0
- Ex p** preparation for pressurization according to DIN EN IEC 60079-2

**Protection Class**

- IP66**                       **IP67**                       **IP68**
- CSA Enclosure Type 4X (NEMA 4X)**

**Vents and Drains** (→ data sheet [KD184](#))

- LF** Labyrinth filter IP44
- DV** Vents and Drains IP66

