

## MINICAB 44

Made of hot-pressed glassfibre reinforced polyester (GRP)  
Low flammability and self-extinguishing

- Door with 1-point locking device
- Hinges of stainless steel (1.4571)
- UV resistant
- EPDM seal
- Colour RAL similar 7032 light grey
- Protection Class IP54
- Weight approx. 9 kg

Dimensions in mm (approx.)	Height 505	Width x 355	x	Depth 256
-------------------------------	---------------	----------------	---	--------------

### Door hinge

- right  left

### Locks and handle variations

- |   |   |
|---|---|
| <input type="checkbox"/> DB<br>(Two-way key bit)  | <input type="checkbox"/> STG<br>(Star handle)                                   |
| <input type="checkbox"/> TGOS<br>(T-handle without lock)                                  | <input type="checkbox"/> TGMS<br>(T-handle with lock)                           |
| <input type="checkbox"/> LGOS<br>(Lever Handle without lock)                              | <input type="checkbox"/> LGMS<br>(Lever Handle with lock)                       |
| <input type="checkbox"/> LGVS<br>(Lever Handle; aluminium, black)<br>for optional padlock | <input type="checkbox"/> LGVAVS<br>(Lever Handle SS316)<br>for optional padlock |
| <input type="checkbox"/> KGPHZ<br>(swiveling compact handle<br>for profile half-cylinder) |   |

### Window (320 x 170 mm)

- FA acrylic glass window  
 FS safety glass window

### Fastening on pipe clamps

Pipe clamp set consisting of RS21 & mounting rails

- Pipe clamp set (1.4571)

### Mounting rail

- stainless Steel (1.4571) or  galvanized steel

- MS 150 Q  MS 21 L  
 MS 150 QS  MS 21 Q

### Mounting plate

- V4A (3 mm)  
 GRP (4,5 mm)

### Wall mounted WA

- WA100 (1.4571)  
 WA100 (galvanized steel)

### Option

- Special colour

### Explosion protection

- GO antistatic to avoid electrostatic charges  
according to DIN EN IEC 60079-0

### Protection Class

- IP65

