




Product Overview 2017 BASIC

Modular design manufactured from fully insulated sandwich, colour RAL7032 (alternatively RAL7035)

- Vertical mounting rail system in anodized aluminium, installed on rear wall (over full room height)
 - Flat roof: GRP with PU-foam core (20 mm thick)
 - Sandwich floor plate (25mm thick) of glassfibre reinforced polyester with PU foam core
- On request: Floor design GRP-Plate 5 mm thick, other floor design => data sheet [SD525](#)



- Standard door handles are lockable lever with 3-point locking mechanism and half profile cylinder (parallel locking)

Type designation, Example: Cabinet Series BASIC 100, Width 840 mm, Depth 600 mm = BASIC 100.080.060

BASIC 100 Height 1045 mm inside height 1000 mm	Width	440mm single door	640mm single door	840mm singledoor	1040mm singledoor	1290mm double door
	Depth					
	300 mm					
	400 mm					
	600 mm					
	800 mm					

all sizes available

Mounting plate, sheet steel 3 mm, galv., with rolled edges, 850 mm high

	Width	345 mm	545 mm	745 mm	945 mm	2x 545* mm
	Price					

BASIC 125, Height 1295 mm inside height 1250mm	Width	640mm single door	840mm single door	1040mm single door	1290mm double door
	Depth				
	300 mm				
	400 mm				
	600 mm				
	800 mm				

all sizes available

Mounting plate, sheet steel 3 mm, galv., with rolled edges, 1100 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm
	Price				

BASIC 150, Height 1545 mm inside height 1500mm	Width	640mm single door	840mm single door	1040mm single door	1290mm double door
	Depth				
	300 mm				
	400 mm				
	600 mm				
	800 mm				

all sizes available

Mounting plate, sheet steel 3 mm, galv., with rolled edges, 1350 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm
	Price				

BASIC 175, Height 1795 mm inside height 1750mm	Width	640mm single door	840mm single door	1040mm single door	1290mm double door
	Depth				
	300 mm				
	400 mm				
	600 mm				
	800 mm				

all sizes available

Mounting plate, sheet steel 3 mm, galv., with rolled edges, 1600 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm
	Price				

BASIC 200, Height 2045 mm inside height 2000mm	Width	640mm single door	840mm single door	1040mm single door	1290mm double door
	Depth				
	300 mm				
	400 mm				
	600 mm				
	800 mm				

all sizes available

Mounting plate, sheet steel 3 mm, galv., with rolled edges, 1850 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm
	Price				

*Mounting plates two-part construction with vertical partition



Product Overview 2017 BASIC

GRP Ground Vault, Height 1005 mm => data sheet SD192								
	Width	440 mm	640 mm	840 mm	1040 mm	1290 mm		
	Depth							
	300 mm							
	400 mm							
	600 mm							
	800 mm							
	SZ 008	Removable cover at the front						
Windows and Locking Mechanisms								
	FA/FS ...	Window, double-glazed for Serie Type => data sheet SD532	Height x Width		Acrylglass	Safety glass		
			740 x 165 mm					
			740 x 255 mm					
			740 x 355 mm					
			740 x 390 mm					
			740 x 555 mm					
			740 x 740 mm					
		740 x 390 u. 740 x 355 mm						
		740 x 390 u. 740 x 390 mm						
	FB052	Double swing handle prepared for installation of a second half profile cylinder => data sheet SD512						
Accessories								
	See PL303 page 3 Options and Configurations for cabinets	Mounting rails c/w brackets and bolts, for horizontal mounting behind the door	Width		galvanized		St. Steel	
			400 mm	SMSS-400-SET		SMSV-400-SET		
			600 mm	SMSS-600-SET		SMSV-600-SET		
			800 mm	SMSS-800-SET		SMSV-800-SET		
			1000 mm	SMSS-1000-SET		SMSV-1000-SET		
		Pair of mounting rails, c/w brackets and bolts vertical mounting behind the door			Anodized aluminium	Further materials see "Product Overview Options and Configurations for Cabinets" page 3		
	SMSA-980	for BASIC 100						
	SMSA-1230	for BASIC 125						
	SMSA-1490	for BASIC 150						
	SMSA-1730	for BASIC 175						
	SMSA-1980	for BASIC 200						
	FS090	Spring nut M6						
	SLKV	Vent Louver, c/w internal slider, installed	Width x Height	Plastic	Alumi- nium	St. Steel	Insect screen St. Steel	
			250 x 80 mm					
			385 x 220 mm					
	SW009							
	SW141-A4							
	SB010-WSA							

Consult factory for other sizes, options and mounting accessories.

- GO (antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0)
- 19" swing frames or swing-out mounting plates, internal doors, adjustable shelves
- Heating
- Electrical lights and electric installations (also for hazardous areas)
- Ventilation, louvers, sunshades
- Bottle storage cabinets with loading ramp and bottle holders

Subject to technical changes, printing errors and price increases due to rising raw material costs. Not all the options can be combined.

Extra fees on mounting. All stainless steel components are made of SS316.

The listed prices are ex works (INCOTERMS 2010), uncleared, packing extra, plus V.A.T. (if applicable).

Prices are subject to change without notice. Payment: 10 days 2 %, 30 days net.

Place of performance is Neustadt on the Donau and jurisdiction is Ingolstadt on the Donau, Germany.