




Product Overview 2017 CLASSIC

Manufactured in modular design, of insulated sandwich-style elements and GRP support posts, colour RAL7032 (alternatively RAL7035)

- Vertical mounting rail system in anodized aluminium, over the full room height
- Flat roof of GRP with PU-foam core (60 mm thick)
- Floor of glassfibre reinforced polyester, with polyurethane foam core (80 mm high)
other floor design => data sheet [SD522](#)
- Standard door handles are lockable lever with 3-point locking mechanism and half profile cylinder (parallel locking)
- Degree of protection is IP65 (with single doors) or IP54 (with double doors)



Type designation, Example: Cabinet Series CLASSIC 110, Width 1350 mm, Depth 900 mm = CLASSIC 110.135.090

CLASSIC 110, Height 1140mm, inside height 1000 mm	Width \ Depth	700 mm	900 mm	1100 mm	1350 mm	1550 mm	1750 mm	1950 mm	2150 mm
		single door	single door	single door	double door	double door	double door	double door	2 single doors
	500 mm								
	700 mm								
	900 mm								
	1100 mm								

all sizes available

Mounting plate, sheet steel 3 mm, galv.,with rolled edges, 850 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm	545+745*mm	2x 745* mm	750+945*mm	2x 945* mm
	Price								

CLASSIC 135, Height 1390mm, inside height 1250 mm	Width \ Depth	700 mm	900 mm	1100 mm	1350 mm	1550 mm	1750 mm	1950 mm	2150 mm
		single door	single door	single door	double door	double door	double door	double door	2 single doors
	500 mm								
	700 mm								
	900 mm								
	1100 mm								

all sizes available

Mounting plate, sheet steel 3 mm, galv.,with rolled edges, 1100 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm	545+745*mm	2x 745* mm	745+945*mm	2x 945* mm
	Price								

CLASSIC 160, Height 1640mm, inside height 1500 mm	Width \ Depth	700 mm	900 mm	1100 mm	1350 mm	1550 mm	1750 mm	1950 mm	2150 mm
		single door	single door	single door	double door	double door	double door	double door	2 single doors
	500 mm								
	700 mm								
	900 mm								
	1100 mm								

all sizes available

Mounting plate, sheet steel 3 mm, galv.,with rolled edges, 1350 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm	545+745*mm	2x 745* mm	745+945*mm	2x 945* mm
	Price								

CLASSIC 185, Height 1890mm, inside height 1750 mm	Width \ Depth	700 mm	900 mm	1100 mm	1350 mm	1550 mm	1750 mm	1950 mm	2150 mm
		single door	single door	single door	double door	double door	double door	double door	2 single doors
	500 mm								
	700 mm								
	900 mm								
	1100 mm								

all sizes available

Mounting plate, sheet steel 3 mm, galv.,with rolled edges, 1600 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm	545+745*mm	2x 745* mm	745+945*mm	2x 945* mm
	Price								

CLASSIC 210, Height 2140mm, inside height 2000 mm	Width \ Depth	700 mm	900 mm	1100 mm	1350 mm	1550 mm	1750 mm	1950 mm	2150 mm
		single door	single door	single door	double door	double door	double door	double door	2 single doors
	500 mm								
	700 mm								
	900 mm								
	1100 mm								

all sizes available

Mounting plate, sheet steel 3 mm, galv.,with rolled edges, 1850 mm high

	Width	545 mm	745 mm	945 mm	2x 545* mm	545+745*mm	2x 745* mm	745+945*mm	2x 945* mm
	Price								

*Mounting plates two-part construction with vertical partition



Product Overview 2017 CLASSIC

GRP Ground Vault - height 1005 mm => data sheet SD292										
	Width	700 mm	900 mm	1100 mm	1350 mm	1550 mm	1750 mm	1950 mm	2150 mm	
	Depth									
	500 mm									
	700 mm									
	900 mm									
	1100mm									
	SZ 008	Removable cover at the front								
Windows										
	FA/ FS / FW ...	Window double-glazed for Cabinet Type... => data sheet SD532	Height x Width				Acrylic Glass	Safety Glass		
			740 x 255 cm				double-glazed			
			740 x 355 mm							
			740 x 390 mm							
			740 x 555 mm							
			740 x 740 mm							
			740 x 390 & 740 x 355 mm							
			740 x 390 & 740 x 390 mm							
			740 x 390 & 740 x 555 mm							
			740 x 390 & 740 x 740 mm							
		740 x 555 & 740 x 740 mm								
		740 x 740 & 740 x 740 mm								
	FB052	Double swing handle (instead of lever) prepared for installation of a second half profile cylinder => data sheet SD512								
	SACP-3PST	Panic bar for walk-in cabinets/shelter								
Accessories										
	SW137	Degree of Protection IP 66 (for cabinets with single door)								
		Mounting rails (Related to the size of the wall panels) with mounting brackets and bolts, horizontally mounted, for wall panels <i>(For one-piece over the entire length or vertically mounted rails refer to our product survey "Options and Configurations for Cabinets")</i> => data sheet SD712	Width		galvanized		St. Steel			
			400 mm	SMSS-400-SET		SMSV-400-SET				
			600 mm	SMSS-600-SET		SMSV-600-SET				
			800 mm	SMSS-800-SET		SMSV-800-SET				
		1000 mm	SMSS-1000-SET	SMSV-1000-SET						
	FS090	Spring nut M6								
	SLKV	Vent louvers with internal sliders, installed	Height x Width		Plastic	Aluminium	St. Steel	Insect screen		
			250 x 80 mm					St. Steel		
			385 x 220 mm							

Other dimensions and designs as well as mounting material upon request:

- 19" swing frames or swing-out mounting plates, internal doors etc.
- Ex p, GO (antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0)
- Heating, Cooling active or passive
- Adjustable shelves
- Inside-electrical lights and electric installations (also for hazardous areas)
- andere Brandklassifizierungen
- Ventilation, louvers, sunshades
- Other locking mechanisms
- Other flammability classifications possible, F30 possible
- EMC: electromagnetic protection
- Bottle storage cabinets with loading ramp and bottle holders
- Special cable and pipe entries

Subject to technical changes, printing errors and price increases due to rising raw material costs.

Extra fees on mounting. All stainless steel components are made of SS316.

Not all the options can be combined.

The listed prices are ex works (INCOTERMS 2010), uncleared, packing extra, plus V.A.T. (if applicable).

Prices are subject to change without notice. Payment: 10 days 2 %, 30 days net.

Place of performance is Neustadt on the Donau and jurisdiction is Ingolstadt on the Donau, Germany