



Product Overview 2017 Options and Configurations for cabinets

Sketch	Type Designation	Description	Cabinet Series						
Materialoptionen									
	GO	Reduced surface resistance , antistatic to avoid electrostatic charges according to DIN EN IEC 60079-0	all						
	F 30	Fire resistance class F 30 , as per DIN 4102, if installed on customer-supplied base plate	CLASSIC						
	Exp	Preparation for a pressurized cabinet to DIN EN IEC 60079-2 Pressure test with inspection certificate	CLASSIC						
Door stays (door aperture angle 105°)									
	STAF-EA4	Door stay with lock-open device	Stainless steel						
	STAT	Telescopic door dampener with adjustable manual brake	all						
	STAG-VZ	Gas strut, automatically pushes the door open		Galvanized steel					
	STAG-E	Gas strut , automatically pushes the door open		Stainless steel					
Wind and weather protection									
	Roof extension (500 mm) with lateral wind protection covers								
	CLASSIC SDWC	Price	Cabinet width (mm)						
			700	900	1100	1350	1550	1750	1950
		CLASSIC 110							
		CLASSIC 135							
		CLASSIC 160							
		CLASSIC 185							
	CLASSIC 210								
	BASIC SDWB	Price	Cabinet width (mm)						
			640	840	1040	1290	1490	1690	1890
		BASIC 100							
		BASIC 125							
BASIC 150									
BASIC 175									
BASIC 200									
Lifting lugs									
	SK002	Installed on the roof, removable type, suitable for empty cabinet or slight additional on the mounting plate; payload 50 kg	Set = 2 pcs	CLASSIC					
	SK004			BASIC					
	SK003	Installed on the roof, removable type, suitable for loads of 250 kgs		CLASSIC					
	SK005			BASIC					
	SKOD-M10	Installed on the roof, with tension rods, suitable for loads of 600 kgs, in case of floor version A for 300 kgs		CLASSIC					
	SKOD-M16				Installed on the roof, with tension rods, suitable for loads of 1,200 kgs				
	SK008-WSA	Lifting and mounting brackets on the floor frame, maximum load 3.000 kg	only with stainless steel floor frame	CLASSIC					
	SK0082-WSA			Crane- & mounting bracket on the floor frame, max. load 6.000 kg, higher loads upon request	CLASSIC				
	SK009	Crane- & mounting bracket at the edge of the floor frame, charge on request		CLASSIC					



Product Overview 2017 Options and Configurations for cabinets

Aluminium frame window with Makrolon glass window, lockable (installation height 39 mm)										
	SF012	Dimensions 400 x 400 mm	excl. Recess	CLASSIC BASIC						
	SF013	Dimensions 600 x 400 mm								
	SF014	Dimensions 800 x 415 mm								
	SF015	Dimensions 800 x 615 mm								
	SF016	Dimensions 800 x 450 mm								
	SF017	Dimensions 800 x 800 mm								
GRP sunshades in sandwich construction, installed over the standard roof										
	SD003	c/w spacers of up to 20 mm maximum	all							
		c/w spacers of > 20 and < 150 mm								
Special designs for analyzer cabinets										
	SA030	Horizontal partition, with one-piece door	CLASSIC 210 BASIC 200							
		Partition top / bottom 1000/ 1000 mm								
	SA029	Horizontal partition, with two separate doors	CLASSIC 210 BASIC 200							
		Partition top / bottom 1000 / 1000 mm								
Equipment for bottle storage cabinets										
	SGOP	Bottle holder in rigid PU-foam with nylon strap, for bottles of up to 225 mm diameter	extra mounting rails see page 3	all						
	SGOE	Bottle holder with stainless steel mounting chain of 600 mm length, for bottles of up to 300 mm diameter								
	SGOE-250	Universal bottle holder, adjustable, with stainless steel mounting chain								
Loading ramp foldable with raised inner floor (aluminium chequer plate)										
	CLASSIC SGOO	Price	Cabinet width (mm)							
				700	900	1100	1350	1550	1750	1950
		Depth (mm)	500							
			700							
			900							
1100										
BASIC SGOO	Price	Cabinet width (mm)								
			640	840	1040	1290	1490	1690	1890	
	Depth (mm)	300								
		400								
		600								
800										
1000										

Subject to technical changes, printing errors and price increases due to rising raw material costs. Not all the options can be combined.

Extra fees on mounting. All stainless steel components are made of SS316.

The listed prices are ex works (INCOTERMS 2010), uncleared, packing extra, plus V.A.T. (if applicable).





Prices are subject to change without notice.

Payment: 10 days 2 %, 30 days net.

Place of performance is Neustadt on the Donau and place of jurisdiction is Ingolstadt on the Donau, Germany



Product Overview 2017 Options and Configurations for cabinets

additional Mounting rails (MS)					
Vertically mounted					
		Ordering designation / Price	Material		
			Anodized aluminium	Stainless steel	Galvanized steel
		BASIC 100/ CLASSIC 110	SMSA-980	SMSV-980	SMSS-980
		BASIC 125/ CLASSIC 135	SMSA-1230	SMSV-1230	SMSS-1230
		BASIC 150/ CLASSIC 160	SMSA-1490	SMSV-1490	SMSS-1480
		BASIC 175/ CLASSIC 185	SMSA-1730	SMSV-1730	SMSS-1730
		BASIC 200/ CLASSIC 210	SMSA-1980	SMSV-1980	SMSS-1980
		CLASSIC 250	SMSA-2380	SMSV-2380	SMSS-2380
Horizontally mounted					
		Ordering designation / Price	Material		
			Stainless steel		Galvanized steel
Related to the size of the wall panels *	Width (mm)	400	SMSV-400-SET	SMSS-400-SET	
		600	SMSV-600-SET	SMSS-600-SET	
		800	SMSV-800-SET	SMSS-800-SET	
		1000	SMSV-1000-SET	SMSS-1000-SET	
One-piece over the entire length	Width (mm)	1350	SMSV-1350-SET	SMSS-1350-SET	
		1550	SMSV-1550-SET	SMSS-1550-SET	
		1750	SMSV-1750-SET	SMSS-1750-SET	
		1950	SMSV-1950-SET	SMSS-1950-SET	
Other length upon request					
* Particularly for BASIC cabinets: in case of laterally-positioned horizontal mounting rails additional vertical rails are required behind the door (see table above)					
Earthing/grounding components					
	SPOT-I	Equipotential bonding till width 2150 mm			
	SPOT-I	Equipotential bonding for bigger cabinets			
	FP062	Equipotential bonding with copperrails 30 x 5 mm			
	SZ117	Lightning protection			
Entries for cable glands and pipe fittings					
	Price	Recess with laminated reinforcement	Recess with removable flange plate		Wall panel compact
			GFP 4 mm thick	Stainless steel 2 mm thick	20 mm thick
	100 x 100 mm				
	200 x 100 mm				
	300 x 200 mm				
	200 x 200 mm				
400 x 200 mm					
Other dimensions upon request					
	SXKL	Cable entry flap with stainless steel frame 200 x 200 mm with internal locking			CLASSIC BASIC