



# Product Overview 2017 Accessories for Cabinets

Sketch	Type Designation	Description	Cabinet Series	
<b>Lighting equipment (damp-proof) 230Volt/ 50Hz</b>				
	<b>SHFR</b>	Fluorescent tube with protective cover, on/off switch and socket-outlet combination and junction box, completely installed in the cabinet	1 x 18 watts, 340 mm long (small)	
			1 x 18 watts, 670 mm long	
			1 x 36 watts, 1280 mm long	
			1 x 58 watts, 1580 mm long	
		<b>Door contact switch</b> instead of on/off switch	all	
	<b>FE102</b>	Extra charge for additional socket		
		<b>Special voltages, LED versions, Ex-Proof versions for hazardous areas or other configurations possible</b>		
<b>Combination of filter fans &amp; exhaust filters, fan allowing air to be blown into or out of cabinet (A) – damp room</b>				
	Supply voltage 230 V/ 50 Hz, IP55, UV-resistant, installed		all	
	<b>SLFL-PF22.000 /...A</b>	Fan 145x145mm		Air volume flow <b>40 cbm/h</b> (unrestricted)
	<b>SLFL-PFA20.000</b>	Exhaust filter		
	<b>SLFL-PF43.000 /...A</b>	Fan 252x252mm		Air volume flow <b>180 cbm/h</b> (unrestricted)
	<b>SLFL-PFA40.000</b>	Exhaust filter		
	<b>SLFL-PF65.000 /...A</b>	Fan 320x320mm		Air volume flow <b>380 cbm/h</b> (unrestricted)
	<b>SLFL-PFA60.000</b>	Exhaust filter		
	<b>FM139</b>	Thermostat RT-SSR 10-60 °C IP30, loose		
<b>FM099</b>	Thermostat AZT-I 5-35 °C IP54, loose			
<b>Combination of filter fans &amp; exhaust filters, fan allowing air to be blown into (B) or out of cabinet (A) – Ex-version</b>				
	Supply voltage 230 V/ 50 Hz, IP54, UV-resistant, installed		all	
	<b>SLFL-EXVENTB/...A</b>	Fan		air volume flow in combination: <b>150 cbm/h</b>
	<b>SLFL-PFA40000GO</b>	Exhaust filter		
	<b>HFZA-0/50</b>	Ex Capillary tube thermostat 0-50 °C IP65, loose		
<b>Floor mounting</b>				
	<b>SB007-WSA</b>	External floor mounting bracket (Set=4 pcs.)		
	<b>SB010-WSA</b>	Internal floor mounting (Set=4 pcs.)		
	<b>SB011-WSA</b>	External floor mounting bracket (Set=4 pcs.)		
	<b>SB035-WSA</b>	Internal floor mounting (Set=4 pcs.)		
	<b>SB059-WSA</b>	Internally with additional anchor plates (Set=4 pcs.)		
	<b>SB020-WSA</b>	Mounting holes, internal (4 pcs.)		
	<b>SB086-WSA</b>	Welded straps, inside, with anchor dowels (1 pc.)		
	<b>SB007-WSA</b>	External mounting bracket (Set=4 pcs.)		
	<b>SK008-WSA</b>	With external lifting bracket (Set=4 pcs.)		
	<b>SK0082-WSA</b>	With external lifting bracket (Set=4 pcs.)		
		Vault mounting (for underground vaults) => data sheet <a href="#">SD192</a> and <a href="#">SD292</a>		
	<b>SB050</b>	Standard mounting set for ground vault (1 set = 4 pcs.) tapered ground screws and fastening bracket suitable for soil classes I, II, III and V		
		Designed for <b>other soil classes</b> or increased requirements		
		INTERTEC stability calculation (customised)		
<b>INTERTEC stability calculation (customised)</b>				
	<b>SW009</b>	Inside		
	<b>SW141-A4</b>	Outside		
	<b>SW001</b>	Outside, for double doors		
	<b>SW001</b>	Outside, CLASSIC 110, width	700 mm	
			900 mm	
			1100 mm	
			1350 mm	
			1550 mm	
			1950 mm	
			BASIC	
			CLASSIC	



## Product Overview 2017 Accessories for Cabinets

Swing-out mounting plates					
	Sheet steel, zinc coated 3 mm thick, with rolled edges, optionally hinged left or right, with double-bit lock and handle for opening, installed behind the door			CLASSIC	BASIC, with extra mounting rails behind the door
	Door (H x W)	Type Designation	Mounting-plates (H x W)		
	1000 x 600	SMPS-1000.400MS	850 x 350 mm		
	1000 x 800	SMPS-1000.600MS	850 x 550 mm		
	1000 x 1000	SMPS-1000.800MS	850 x 750 mm		
	1000 x 1200	SMPS-1000.1000MS	850 x 950 mm		
	1250 x 800	SMPS-1250.600MS	1100 x 550 mm		
	1250 x 1000	SMPS-1250.800MS	1100 x 750 mm		
	1250 x 1200	SMPS-1250.1000MS	1100 x 950 mm		
	1500 x 800	SMPS-1500.600MS	1350 x 550 mm		
	1500 x 1000	SMPS-1500.800MS	1350 x 750 mm		
	1500 x 1200	SMPS-1500.1000MS	1350 x 950 mm		
	1750 x 800	SMPS-1750.600MS	1600 x 550 mm		
	1750 x 1000	SMPS-1750.800MS	1600 x 750 mm		
	1750 x 1200	SMPS-1750.1000MS	1600 x 950 mm		
2000 x 800	SMPS-2000.600MS	1850 x 550 mm			
2000 x 1000	SMPS-2000.800MS	1850 x 750 mm			
2000 x 1200	SMPS-2000.1000MS	1850 x 950 mm			
Special designs or stainless steel					
Swing-out mounting plates, depth-adjustable					
	Prices as before, however extra charge due to four additionally required horizontal mounting rails, see "Pricelist: Options and Configurations for Cabinets" page 3, <a href="#">or, for more detailed information =&gt; data sheet SD726</a>				
19" Profiles, stainless steel, mounted behind the door					
	SM269	For door widths 600 mm	BASIC/ CLASSIC		
		For door widths 1000 mm (Option with side covers)			
		Other door widths			
19" Profiles, stainless steel, depth adjustable					
	Prices as above, however extra charge due to 4 additionally required horizontal mounting rails, see "Pricelist: Options and Configurations for Cabinets" page 3				
19"-Swing frame, stainless steel, installed in twin beams, hinged left or right, lockable					
	SM268	Without side covers	BASIC/ CLASSIC		
		With side covers, left <u>and</u> right			
		With side cover, left <u>or</u> right			
19"-Swing frame, stainless steel, depth adjustable, installed in twin beams, hinged left or right, lockable					
	Prices as above, however extra charge due to 4 additionally required horizontal mounting rails, see "Pricelist: Options and Configurations for Cabinets" page 3, <a href="#">or for more detailed information =&gt; data sheet SD732</a>				

\* RU = rack unit = 1 3/4 inch = 44,45 mm

For other mounting arrangements and accessories consult factory. Extra fees on mounting. All stainless steel components are made of SS316.

Subject to technical changes, printing errors and price increases due to rising raw material costs. Not all the options can be combined.

The listed prices are ex works (INCOTERMS 2010), uncleared, packing extra, plus V.A.T. (if applicable).

Prices are subject to change without notice. Payment: 10 days 2 %, 30 days net.

Place of performance is Neustadt on the Donau and place of jurisdiction is Ingolstadt on the Donau, Germany